



# PRI Construction Materials Technologies LLC

6412 Badger Drive  
Tampa, FL 33610  
813.621.5777  
<https://www.pri-group.com/>

## Laboratory Test Report

**Report for:** Richard Spreen  
Shredded Tire, Inc.  
6680 MW 17<sup>th</sup> Ave  
Ft. Lauderdale, FL 33309

**Product Name:** 6" 22GA SS Drip Edge adhered to Echo Flow and Echo Block

**Project No.:** 1957T0004

**Dates Tested:** Nov. 10, 2020

**Test Methods:** ANSI/SPRI ES-1 (2003) RE-2  
ANSI/SPRI/FM 4435/ES-1 (2011) RE-2

**Results Summary:** Passing load: -125psf

**Purpose:** Testing was conducted to evaluate the named product for performance in accordance with **ANSI/SPRI ES-1 Wind Design Standard for Edge Systems Used in Low Slope Roofing Systems, SPRI Test RE-2 Pull-Off Test for Edge flashings.**

**Test Methods:** Testing was conducted as described in **ANSI/SPRI Wind Design Standard for Edge Systems Used in Low Slope Roofing Systems, SPRI Test RE-3 Pull-Off Test for Copings (2003)** and **ANSI/SPRI/FM 4435/ES-1 Wind Design Standard for Edge Systems Used with Low Slope Roofing Systems, RE-2 Pull-Off Test for Edge flashings (2011).**

**Sampling:** The following materials were received by PRI.

<u>Product</u>	<u>Origin</u>	<u>Date</u>
6" 22GA SS Drip Edge	Ft. Lauderdale	Oct. 20, 2020
20GA SS Steel Sheet	Ft. Lauderdale	Oct. 20, 2020
Echo Block	Ft. Lauderdale	Oct. 20, 2020
Echo Flow	Ft. Lauderdale	Oct. 20, 2020
ICP Adhesives' Polyset AH-160	Ft. Lauderdale	Oct. 20, 2020

**Description:**

Drip Edge: 22 ga., 304 Stainless Steel; Attached to Echo block along the top of the block with 1-5/8" OMG HeadLok SP fasteners installed 9" o.c. along the top flange, 1" from the edge. Vertical face adhered to Echo Block and Echo Flow with a single 1.5" to 2" bead of ICP Adhesives' Polyset AH-160. See Appendix A for drawing.

Substrate: 6" wide 20GA 304 stainless steel sheet adhered to the wood nailer with ICP Adhesives' Polyset AH-160 by applying a 1.5" to 2" bead. 3" x 6" x 24" Echo Flow blocks and 3.5" x 6" x 24" Echo Blocks adhered to the steel sheet with ICP Adhesives' Polyset AH-160 by applying a 1.5" to 2" bead. See Appendix A for drawing.

1957T0004A

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.

**Results:** Horizontal loads were applied in 15 psf increments up to 150 psf or until failure. Horizontal loads applied above 150 psf were applied in 10 psf increments until failure, as applicable. Passing load is the maximum load that was sustained for 60 seconds. Detailed drawings are contained Appendix A.

	Results
Passing Load (psf)	-125
Failing Load (psf)	-150
Time of Failure (s)	3
Failure Mode	Echo Flow adhesion

Note(s): None.

**Statement of Attestation:**

The edge metal performance was evaluated in accordance with **ANSI/SPRI Wind Design Standard for Edge Systems Used in Low Slope Roofing Systems, SPRI Test RE-2 Pull-Off Test for Edge flashings (2003)** and **ANSI/SPRI/FM 4435/ES-1 Wind Design Standard for Edge Systems Used with Low Slope Roofing Systems, RE-2 Pull-Off Test for Edge flashings (2011)**. The test results are representative of the materials received and prepared as described herein.


Signed:   
 \_\_\_\_\_  
 Zachary Priest, P.E.  
 Director

**Report Issue History:**


Issue #	Date	Pages	Revision Description (if applicable)
Original	11/12/2020	4	NA

1957T0004A

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.




CLARIFICATION PURPOSES ONLY  
 FASTENING PATTERN FOR 20 GA. STAINLESS STEEL  
 1" FROM THE EDGE, 12" INCHES ON CENTER FASTENED W/ 1-5/8" OMG HEADLOK SP



**Figure 1. Installation of Drip Edge**

1957T0004A

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.



**END OF REPORT**

1957T0004A

The test results, opinions, or interpretations are based on the material supplied by the client. This report is for the exclusive use of stated client. No reproduction or facsimile in any form can be made without the client's permission. This report shall not be reproduced except in full without the written approval of this laboratory. PRI Construction Materials Technologies LLC assumes no responsibility nor makes a performance or warranty statement for this material or products and processes containing this material in connection with this report.